



LINE-INTERACTIVE UPS ECO II 1000 LED

➤ KEY FEATURES

- Wide Input Range 145-280Vac
- 4 x Thai Universal outlets
- Automatic Voltage Regulation (AVR)
- Auto-restart/Auto-charge
- LED display
- Generator Compatible
- Cold Start Function
- Off-mode Charging
- Optional USB/RS232 Communication Port & RJ-11/RJ-45 Protection

Model Name	ECO II 1000 LED
Capacity	1000VA/630W
Input	
Voltage	220V
Voltage Range	145-280V
Frequency	50/60Hz (Auto Sensing)
Output	
Voltage	220V220V±10% for online mode 220V±5% for Battery mode
Frequency (Battery)	50/60Hz±1%
Waveform (Battery)	Simulated Sine Wave
Transfer Time	2ms Typical
Overload Protection	>110% alarm 1 min then shutdown, >120% shut down immediatly
Battery	
Battery Type	Sealed Lead-acid Maintenace Free
Battery Voltage	12V
Total Battery Quantity	1
Backup Time	Backup time 15-30 mins (depend of load)
Indicators	
Display	LED
Alarm	Battery Mode, Low Battery, Overload, Fault, etc.
Interface	
RS232	N/A
HID Compliant USB Port	N/A
TVSS	N/A
Management	
Auto Recharge	Yes
Auto Restart	Yes
Power Management Software	Yes
Physical	
Dimensions (W x H x D)(mm)	96 x 138 x 286
Net Weight (kg)	6.5
Environment	
Operating Humidity	0-90% Non-condensing
Operating Temperature	0-40°C



The Sun Power Co.,Ltd.

31 Soi Prachautit 59, Yeak 5, Tel. 02-872-9501/4 Fax.02-872-9505
Bangmod,Thungkru, WWW.THESUNPOWER.CO.TH
Bangkok 10140 THAILAND. Email. SaleContact@thesunpower.co.th