



## LINE-INTERACTIVE UPS ECO II 1000

### > KEY FEATURES

- Wide Input Range 145-280Vac
- 4 x Thai Universal outlets
- Automatic Voltage Regulation (AVR)
- Auto-restart/Auto-charge
- LED/LCD Panels (Optional)
- Generator Compatible
- Cold Start Function
- Off-mode Charging
- Optional USB/RS232 Communication Port & RJ-11/RJ-45 Protection

Model Name	ECO II 1000
Capacity	1000VA/630W
<b>Input</b>	
Voltage	220V
Voltage Range	145-280V
Frequency	50/60Hz (Auto Sensing)
<b>Output</b>	
Voltage (Battery)	220V±10%
Frequency (Battery)	50/60Hz±1%
Waveform (Battery)	Simulated Sine Wave
Transfer Time	2ms Typical
Overload Protection	>110% alarm 1 min then shutdown, >120% shut down immediatly
<b>Battery</b>	
Battery Type	Sealed Lead-acid Maintenace Free
Battery Voltage	12V
Total Battery Quantity	1
Backup Time	Backup time 15-30 mins (depend of load)
<b>Indicators</b>	
Display	LED/LCD
Alarm	Battery Mode, Low Battery, Overload, Fault, etc.
<b>Interface</b>	
RS232	Optional
HID Compliant USB Port	Yes for LCD
TVSS	Optional
<b>Management</b>	
Auto Recharge	Yes
Auto Restart	Yes
Power Management Software	Yes
<b>Physical</b>	
Dimensions (W x H x D)(mm)	96 x 138 x 286
Net Weight (kg)	6.5
<b>Environment</b>	
Operating Humidity	0-90% Non-condensing
Operating Temperature	0-40°C



**The Sun Power Co.,Ltd.**

31 Soi Prachautit 59, Yeak 5, Tel. 02-872-9501/4 Fax.02-872-9505  
Bangmod,Thungkru, WWW.THESUNPOWER.CO.TH  
Bangkok 10140 THAILAND. Email. SaleContact@thesunpower.co.th